

navigo

12VS

Open FiberglassTenders



	Overal Length	:	12′/ 3.66m	Number of Chambers	:	3 + 1	Shaft Length Option 1: 15"/ 38.1cm
S P E C S	Overal Beam	:	6′/ 1.82m	Person Capacity	:	6	Shaft Length Option 2 : 20" / 50.8cm
	Inside Length	:	8′9″/ 2.67m	Weight	:	198lb / 90kg	RDC Design Category : C
	Inside Beam	:	2´9″/ 0.84m	Recommended HP	:	20hp / 14.9kw	
	Tube Diameter	:	18"/ 0.46m	Maximum HP	:	30hp / 22.4kw	

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Bow Locker/ Seat

ΩS

പ ന A R

z⊢

 $\triangleleft \triangleleft$

μш

νц

<u>ہ ר</u>

∢ш

Zĸ

0⊃

⊢∢

പപ

Оц

- Diamond Shape Non - Skid Deck

- Plastic External Transom Plate Aluminum Internal Transom Plate with Security Lip Orca (CSM) Five Layer Coated Fabric 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Double Rub Rail
 Stainless Steel Bow Eye

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug

- Deck Condensation Plug Hand Pump Deck Drain with Plug Maintenance Kit 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes Owner's Manual 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes Additional Air Retaining Chamber Under the Floor 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes 3 Layer Reinforced Seams Paddle with Aluminum Shaft
- Paddle HoldersRemovable Stern SeatHand Pump

- Bow Hatch Cushion
- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat

- Removable Rowing Seat
- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit

