

## navigo

## 13VS

## **Open FiberglassTenders**



	Overal Length	:	13′/ 3.96m	Number of Chambers	:	3 + 1	Shaft Length	:20"/ 50.8cm
S P E C S	Overal Beam	:	6′4″/ 1.94m	Person Capacity	:	7	RDC Design Category	: C
	Inside Length	:	9′9″/ 2.97m	Weight	:	293lb / 133kg		
	Inside Beam	:	3´1″/ 0.94m	Recommended HP	:	30hp / 22.4kw		
	Tube Diameter	:	18″/ 0.46m	Maximum HP	:	40hp / 29.8kw		

- Hand Laid Fiberglass Deep "V" Hull
  Stringer System Laminated into Hull
  Bow Locker/ Seat

Ωv

പ ന ΑĽ

z⊢

 $\triangleleft \triangleleft$ 

μш

νц

<u>ہ ר</u>

∢ш

ZĽ

0⊃

⊢∢

പപ Оц

· —

- Diamond Shape Non - Skid Deck
- Plastic External Transom Plate

- Aluminum Internal Transom Plate Orca (CSM) Five Layer Coated Fabric 3 Push Plastic Non-Corrosive 2 Stage Inflation Valves

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

Raised Double Rub Rail
 Stainless Steel Bow Eye

Bow Hatch Cushion

Removable Rowing Seat

Boat Cover

Chock Set

- 4 Stainless Steel Davit Lifting Points
  Stainless Steel Towing Rings & Tie Downs
  Deck Condensation Plug

- Deck Origensator Frug Deck Drain with Plug 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft Paddle Holders

## Bimini Top

- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit



- Removable Stern Seat
  Hand Pump
  Maintenance Kit Owner's Manual Additional Air Retaining Chamber Under the Floor