navigo

9VS

## Open FiberglassTenders



Number of Chambers : 3 + 1

: 4

: 143lb / 65kg

: 9.9hp / 7.4kw

ے

S

A A ∢ <  $\vdash$   $\sqcup$ SH

0 н

 Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hu Stringer System Laminated into Hull Bow Locker/ Seat Diamond Shape Non - Skid Deck

**Overal Length** 

**Overal Beam** 

Inside Length

Inside Beam

Tube Diameter

Plastic External Transom Plate
Aluminum Internal Transom Plate with Security Lip
Orca (CSM) Five Layer Coated Fabric
3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

: 9'6"/ 2.90m

: 5'7"/1.72m

: 6'9"/ 2.06m

: 2'8"/ 0.81m

Raised Double Rub Rail Stainless Steel Bow Eye

: 17"/ 0.43m Maximum HP : 15hp / 11.2kw

**Person Capacity** 

Recommended HP

Weight

4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug

1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes Maintenance Kit
2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes Owner's Manual
2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes Additional Air Retaining Chamber Under the Floor
3 Layer Reinforced Seams
Oarlock Bases

Telescopic Oars with Aluminum Shaft Paddle Holders Removable Rowing Seat

RDC Design Category : C

Shaft Length

: 15" / 38.1cm

Bow Hatch Cushion

**Tube Chaps** 

Boat Cover

Chock Set

■ Bow Step with Fold Down Stainless Steel Cleat

■ Lateral Fold Down Stainless Steel Cleat

■ Removable Stern Seat

■ Bimini Top

