

Alumina - Console Tenders



AB Inflatable Boats January 1, 2008

Leisure Series Boats

Alumina Aluminum Console Tenders

Combining the sporty and stylish design of our Oceanus series with the durability and light weight of our Lammina series, the Alumina line is ideal for those those require a rugged, yet lightweight tender. Our Alumina series offers a full-featured console tender that is light enough to meet the requirements of limited capacity davits.

Each Alumina model is equipped with a heavy-duty aluminum hull that will resist abrasions from rocky shores, coral, and sandy beaches. The light weight of this hull also means that Alumina boats claim excellent fuel economy, and can reach cruising speed with less horsepower. In addition, the Alumina series features comfortable upholstered seating, smartly designed fiberglass consoles, ample storage space, and an integrated fuel tank at the bow for better weight distribution and easier planning. With the Alumina line, boaters can finally have all the amenities of a console tender in an ultra-lightweight and rugged package.

Standard Features Include:

- Battery Tray
- Bow Eye
- Bow Step w/ Fold-Down S/S Mooring Cleat
- Bow Stowage Hatch w/ Cushion
- Console
- · Console Front Access Lid
- · Davit Lifting Points
- Fiberglass Lateral Step w/ S/S Cleat
- Fold-Down Stern Cushioned Seat & Stowage
- Hand Pump
- · Heavy Duty Double Rub Rail
- Hypalon Grab Handles
- · Integrated Fuel Tank at Bow
- Maintenance Kit
- Navigation Lights
- Non-Skid Deck
- Orca Hypalon Five Coated Fabric
- Owners Manual

11ALX and 12 ALX

- S/S Console Rail
- S/S Stern Towing Rings
- · Steering System
- Transom Protector

13ALX, 14ALX, and 15ALX

- S/S Console Grab Handle
- S/S Stern Towing Rings
- Steering System
- Transom Protector

Optional Equipment:

- Boat Cover
- CD/Radio System
- Compass

- Depth & Fish Finder
- Engine
- · Fire Extinguisher

- GPS
- Tilt Steering Wheel
- VHF Package

	11ALX	12ALX	13ALX	14ALX	15ALX
Length	11' 0" (3.35m)	12' 0" (3.65m)	13' 0" (3.90m)	14' 0" (4.30m)	15' 0" (4.58m)
Beam	6' 1" (1.85m)	6' 1" (1.85m)	6' 3" (1.90m)	6' 3" (1.90m)	6' 3" (1.90m)
Ins. Length	8' 5" (2.58m)	9' 6" (2.89m)	10' 6" (3.18m)	11' 9" (3.58m)	12' 10" (3.78m)
Ins. Beam	2' 10" (0.86m)	2' 10" (0.86m)	3' 0" (0.91m)	3' 0" (0.91m)	3' 0" (0.91m)
Internal Area	23.9 ft ² (2.20 m ²)	26.7 ft ² (2.50 m ²)	31.1 ft ² (2.90 m ²)	35.0 ft ² (3.30 m ²)	37.0 ft ² (3.40 m ²)
Weight	282 lb (128kg)	300 lb (136kg)	328 lb (149kg)	351 lb (159kg)	362 lb (164kg)
Max Person Cap.	5	6	7	8	9
Tube Diameter	18" (0.46m)	18" (0.46m)	19" (0.48m)	19" (0.48m)	19" (0.48m)
Shaft Length	20"	20"	20"	20"	20"
Shaft Twin Engines	n/a	n/a	n/a	n/a	n/a
Max Weight Cap.	1847 lb (838kg)	1949 lb (884kg)	2044 lb (927kg)	2130 lb (966kg)	2330 lb (1057kg)
Rec'd HP	20hp (14.9kw)	25hp (18.8kw)	25hp (18.8kw)	30hp (22.4kw)	30hp (22.4kw)
Max HP	30hp (22.4kw)	30 hp (22.4kw)	40 hp (29.8kw)	40hp (29.8kw)	50hp (37.5kw)
No. of Air Chambers	3 + 1	3 + 1	3 + 1	4 + 1	5 + 1
Fuel Tank Cap.	9.2 gal (35 lt)	9.2 gal (35 lt)	14.5 gal (55 lt)	14.5 gal (55 lt)	14.5 gal (55 lt)









