



S P E C S

Overall Length	: 8'6" / 2.60m	Number of Chambers	: 3 + 1	Shaft Length	: 15" / 38.1cm
Overall Beam	: 5'4" / 1.64m	Person Capacity	: 4	RDC Design Category	: C
Inside Length	: 5'10" / 1.79m	Weight	: 125lb / 57kg		
Inside Beam	: 2'4" / 0.72m	Recommended HP	: 8hp / 6.0kw		
Tube Diameter	: 16" / 0.40m	Maximum HP	: 10hp / 7.5kw		

S T A N D A R D
F E A T U R E S

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull
- Bow Locker/ Seat
- Diamond Shape Non - Skid Deck
- Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip
- Orca (CSM) Five Layer Coated Fabric
- 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Double Rub Rail
- Stainless Steel Bow Eye
- 4 Stainless Steel Davit Lifting Points
- Stainless Steel Towing Rings & Tie Downs
- Deck Condensation Plug
- Deck Drain with Plug
- 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Oarlock Bases
- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Removable Rowing Seat
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor

O P T I O N A L
F E A T U R E S

- Bow Hatch Cushion
- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat

